



PALMX



Thermal Transfer / Direct Thermal


TXP-400

- Print speed up to 127mm/s
- Support TSPL, EPL, ZPL, DPL commands
- Support multiple material printing
- Ribbon roll capacity 300m(Outer roll ribbon)



TXP-400

Thermal Transfer/ Direct Thermal



Model	TXP-400
Resolution	203 DPI
Print method	Thermal Transfer / Direct Thermal
Print speed	127 mm (5") / s Max.
Max.print width	104 mm (4.09")
Max.print length	1778 mm (70")

Media	
Media type	Continuous, gap, black mark, fan-fold and punched hole
Media width	25.4~118mm (1.0"~4.6")
Media thickness	0.06~0.254 mm (2.36~10mil)
Media core diameter	25.4 ~ 76.2 mm (1" ~ 3")
Label length	10 ~ 1778 mm(0.39" ~ 70")
Label roll capacity	127 mm (5") OD (External Diameter)
Ribbon capacity	Max.300m
Ribbon width	110 mm

Performance Features	
Processor	32-bit CPU
Memory	8MB Flash Memory/ 8MB SDRAM/ Flash memory can be expanded Max.4GB
Interface	USB+Lan
Sensors	① Gap sensor ② Cover opening sensor ③ Black mark sensor ④ Ribbon sensor

Fonts/Graphics/Symbologies	
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.
1D barcode	Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
2D barcode	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Rotation	0°、90°、180°、270°
Emulation	TSPL、EPL、ZPL、DPL

Physical Features	
Dimension	282 mm (D) x 232 mm (W) x 171 mm (H)
Weight	2.56 kg

Reliability	
Print head life	30 km

Software	
Driver	Windows / Linux / Mac
SDK	Windows / iOS / Android

Power supply	
Input	AC 110-240V,1.8A, 50-60Hz
Output	DC 24V, 2.5A, 60W

Options	
Factory Options	① WiFi module ③ Lan ② RS-232C (2400-115200 bps) communication interface; ④ Serial
Dealer Options	① External paper roll holder and 1" paper roll ③ Cutter ② Extension board for external paper roll holder ④ Peeling machine

Environmental Conditions	
Operation	5 ~ 40°C(41~104°F), Humidity: 25 ~ 85% non-condensing
Storage environment	-40 ~ 60°C(-40~140°F), Humidity:10 ~ 90% non-condensing

